JIANGXI HITO SILICONE MATERIALS CO.,LTD



No 6 Tianhong road,Xinghuo industry zone,Yongxiu, Jiujiang,Jiangxi province,China (86)792-3170318(Tel) (86) 792-3170355 (Fax)

TECHNICAL DATA SHEET

HV-100 Vinyl Silicone Oil

DESCRIPTION

HV-100 Vinyl silicone oil Good activity, cross-linked with hydrogen-containing silicone oil, based on different viscosity, vinyl content and other additives, it can make LSR with different hardness and mechanical properties.

TYPICAL PROPERTIES

	The state of the s	Part .	The state of the s
ITEM	Vinyl %	Volatile % (150℃/3h)	D3~D10 (mg/kg)
HV-100	1.05±0.03	≤0.2	≤300
HV-350	0.5±0.02	≤0.2	≤300
HV-500	0.43±0.02	≤0.2	≤300
ITEM	Vinyl %	Volatile % (200℃/4h)	D3~D10 (mg/kg)
HV-1000	0.32±0.02	≤0.5	≤300
HV-3500	0.2±0.02	≤0.5	≤300
HV-7500	0.16±0.02	≤0.5	≤300
HV-20000	0.1±0.01	≤0.5	≤300
HV-60000	0.08±0.01	≤0.5	≤300
HV-100000	0.007±0.002	≤0,5	≤300

USES AND APPLICATION

Two-stage vulcanization-free products, medical silica gel, baby silica gel, clothing screen printing glue, electronic silica gel and composite products that cannot be baked

SAFETY

Before handling, read the Material Safety Data Sheet and container label for safe use, physical and health hazard information.

STORAGE AND SHELF LIFE

After sealing packaging products stored in a cool, dry place , HV-100 has a shelf life of 36

months from date of manufacture.

PACKAGING

HV-100 is available in 200L drum and 1000L IBC or others.

LEGAL DISCLAIMER

Hito chenical believes that the information in this technical data sheet is an accurate description of the typical uses of the product. Hito Chemical , however, disclaims any liability for incidental or consequential damages, which may result from the use of the product that are beyond its control. Therefore, it is the user's responsibility to thoroughly test the product in their particular application to determine its performance, efficacy and safety. Nothing contained herein is to be considered as permission or a recommendation to infringe any patent or any other intellectual property right.



is a registered trademark of Hito chemical , China.